

NINJA 650 ABS


ORANGE

GREEN (SPECIAL EDITION)

Please note the image shown above is for illustration purposes only.

Specifications			
ENGINE		FRAME	
Type	Liquid-cooled, 4-stroke Parallel Twin, DOHC, 8 valves	Type	Trellis, high-tensile steel
Displacement	649 cm ³	Caster (rake)	24.0°
Bore and Stroke	83.0 mm x 60.0 mm	Tyre:	
Compression Ratio	10.8:1	a) Front	120/70 ZR 17M/C (58W)
Performance:		b) Rear	160/60 ZR 17M/C (69W)
a) Maximum power	50.2 kW {68PS} / 8,000 min ⁻¹	Steering angle (left/right)	32° / 32°
b) Maximum torque	65.7 N.M {6.7kgf.m} / 6,500 min ⁻¹		
Fuel System	Fuel injection : Ø36mm x 2 with dual throttle valves	SUSPENSION	
Ignition	Digital	Front: Type	Ø41 mm telescopic fork
Starting	Electric	Rear: Type	Horizontal Back-link with adjustable preload
Lubrication	Forced lubrication, semi-dry sump	BRAKES	
DRIVE TRAIN		Front: Type	Dual semi-floating Ø300 mm petal discs
Transmission	6-speed, Return	Caliper	Dual piston
Final Drive	Chain	Rear: Type	Single Ø220 mm petal disc
Gear ratios:		Caliper	Single-piston
1st	2.438 (39/16)	DIMENSIONS	
2nd	1.714 (36/21)	Overall length	2,115 mm
3rd	1.333 (32/24)	Overall width	740 mm
4th	1.111 (30/27)	Overall height	1,135 mm
5th	0.966 (28/29)	Wheelbase	1,410 mm
6th	0.852 (23/27)	Ground clearance	130 mm
Final reduction ratio	3.067 (46/15)	Seat height	790 mm
Clutch	Wet multi-disc, manual	Curb mass	193 kg
		Fuel capacity	15 litres

Kawasaki Motors (Malaysia) Sdn. Bhd. reserves the right to alter specifications without prior notice.